

Declaration of Performance (DoP)

Product Type:	Insert appliance
Type, batch or serial number:	
	Jøtul I 18 Panorama, Jøtul I 18 Harmony
Intended use of the product:	Insert burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS
	Postboks 1411, 1602 Fredrikstad, Norway
	Tel.: +47 69 35 90 00
	E-mail: post@jotul.no
AVCP:	System 3
System(s) of assessment and verification of constancy op	
performance (AVCP) of the construction product as set out in	
CPR, Annex V Notified body:	Rhein-Ruhr Feuerstätten Prüfstelle
NB-No:	1625
Test report no:	RRF - 29 03 497
Declared performance:	
Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm
	Floor = 257
	Front = 1000
	Combustable materials inside the surround must be
	covered by insulation as decriebed in the manual
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,09 %]
Surface temperature	Page
Electrical safety	Pass -
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [278°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	10 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [81%]

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, August 23rd 2013

(Place and date of issue)

(Signature)